

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 07-03-2018

Revision Number 3.1

Page 1/8

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Identifier Product Name

1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

Other means of identification Synonyms

No information available

#### Recommended use of the chemical and restrictions on use

Identified uses Lubricant

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Manufacturer Lubrication Engineers Inc. 1919 E. Tulsa Wichita, KS 67216 USA 800-537-7683 Emergency Telephone Number

CHEMTREC: 1-800-424-9300 (NORTH AMERICA) +1-703-527-3887 (INTERNATIONAL)

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 07-03-2018

Revision Number 3.1

# 2. HAZARDS IDENTIFICATION

**Classification** 

### **OSHA Regulatory Status**

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### Label Elements

	Emergency Overview Signal Word	]
	None	
	None	
	Hazard Statements	
	None	
The product contains no s	ubstances which at their given concentration, are consider	red to be hazardous to health
appearance red	Physical state Paste	Odor Hydrocarbon-like
Processioners Statemente Dress	antion	
Precautionary Statements - Prevention Prevention - Preven	ention	
Response		
None.		
Eyes		
None.		
Skin		
None.		
Inhalation		
None.		
Ingestion		
None.		
Fire		
None.		
Spill		
None.		
Storage		
None.		
Disposal		
None.		
Hazards not otherwise classified	(HNOC)	
None	<u></u>	

· May be harmful in contact with skin

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Diacetone alcohol	123-42-2	1 - 5

# **1251 ALMASOL® HIGH TEMPERATURE** LUBRICANT

Issuing Date 04-24-2012	Revision Date 07-03-2018	Revision Number 3.1
Butylated Hydroxy Tolue	ne 128-37-0	0.1 - 1
The producer of "1251" declares that	it contains less than 3% DMSO extractable material by IP-3	46
4. FIRST AID MEASURES		
First Aid Measures		
General Advice	If symptoms develop move victim to fresh air. Show this safety data sheet to the doctor in attendance. Do not breathe dust/fume/gas/mist/vapors/spray.	
Eye Contact	Rinse thoroughly with plenty of water, also under the eyel rinsing.	ids. Keep eye wide open while
Skin Contact	Consult a physician if necessary. Wash off immediately w removing all contaminated clothes and shoes.	ith soap and plenty of water
Inhalation	Move to fresh air. Consult a physician. If not breathing, give	ve artificial respiration.
Ingestion	May cause adverse kidney effects. Drink plenty of water. Do NOT induce vomiting.	
Protection of First-aiders	Use personal protective equipment.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	None known.	
Indication of any immediate medica	al attention and special treatment needed	
Notes to Physician	Treat symptomatically.	
5. FIRE-FIGHTING MEASURE	S	
Flash Point	287 °C / 550 °F	
Suitable Extinguishing Media	uitable Extinguishing Media Water spray, Carbon dioxide (CO2), Foam, Dry chemical	
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire.	
Specific Hazards Arising from the Chemical	Thermal decomposition can lead to release of irritating gases and vapors.	
<u>Explosion Data</u> Sensitivity to Mechanical Impac Sensitivity to Static Discharge	t Not impact sensitive. May be ignited by friction, heat, sparks or flames.	
Protective Equipment and Precautions for Firefighters	Wear self-contained breathing apparatus and protective s	uit.
NFPA Health haz	ard 1 Flammability 1 Stability 1	
6. ACCIDENTAL RELEASE N	EASURES	

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012	Revision Date 07-03-2018	Revision Number 3.1
Personal Precautions	Do not touch or walk through spilled material. Remove all sources of ignition.	
Environmental Precautions		
Environmental Precautions	Prevent entry into waterways, sewers, basements or confined are accumulating to form explosive concentrations. Vapors can accur	
Methods and material for contair	ment and cleaning up	
Methods for Containment	Prevent further leakage or spillage if safe to do so. Absorb spill was sand or earth), then place in a chemical waste container.	ith inert material (e.g. dry
Methods for Cleaning up	Use personal protective equipment. Take up mechanically and collect in suitable containe for disposal. Clean contaminated surface thoroughly.	
7. HANDLING AND STORA	ORAGE	
Precautions for safe handling		
Advice on safe handling	Avoid contact with skin, eyes and clothing. Wear personal protect vapor buildup by providing adequate ventilation during and after us moke when using this product.	
Conditions for safe storage, inclu	uding any incompatibilities	
Technical measures/Storage	Keep container tightly closed in a dry and well-ventilated place. K	eep out of the reach of

Technical measures/Storage<br/>conditionsKeep container tightly closed in a dry and well-ventilated place. Keep out of the reach of<br/>children.Incompatible products.Strong oxidizing agents. Strong acids. Strong bases.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Control parameters

### Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Diacetone alcohol	TWA: 50 ppm	TWA: 50 ppm	IDLH: 1800 ppm
123-42-2		TWA: 240 mg/m <sup>3</sup>	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 240 mg/m <sup>3</sup>
		(vacated) TWA: 240 mg/m <sup>3</sup>	-
Butylated Hydroxy Toluene	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
128-37-0	_		-
Silica, quartz	TWA: 0.025 mg/m <sup>3</sup>	TWA: 50 µg/m <sup>3</sup>	IDLH: 50 mg/m <sup>3</sup>
14808-60-7	_	(vacated) TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup>
Mica (mineral)	TWA: 3 mg/m <sup>3</sup>	(vacated) TWA: 3 mg/m <sup>3</sup>	IDLH: 1500 mg/m <sup>3</sup>
12001-26-2	-		TWA: 3 mg/m <sup>3</sup>
Titanium Dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup>	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7		(vacated) TWA: 10 mg/m <sup>3</sup>	-
Iron Oxide	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	IDLH: 2500 mg/m <sup>3</sup>
1309-37-1	-	TWA: 15 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
		TWA: 5 mg/m <sup>3</sup>	-
		(vacated) TWA: 10 mg/m <sup>3</sup>	
		(vacated) TWA: 5 mg/m <sup>3</sup>	

### Appropriate engineering controls

**Engineering Measures** 

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

## Issuing Date 04-24-2012

Revision Date 07-03-2018

Revision Number 3.1

	Eyewash stations Ventilation systems.	
Individual protection measures, such as personal protective equipment		
Eye/Face Protection	Tightly fitting safety goggles.	
Skin and Body Protection	Long sleeved clothing. Protective gloves.	
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.	
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Physical state	Paste
appearance	red
Odor	Hydrocarbon-like
Odor threshold	No information available
Property	Property
рН	6 - 8
Melting point/freezing point	No data available
Boiling Point/Range	no data available
Flash Point	287 °C / 550 °F
upper flammability limit	No data available
Lower Flammability Limit	No data available
Vapor pressure	No data available
Vapor Density	< 1(Air = 1)
Specific Gravity	0.95
Water solubility	negligible
Partition Coefficient: n-octanol/water	no data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity, kinematic	not applicable

# **10. STABILITY AND REACTIVITY**

reactivity	No information available
Chemical stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Heat, flames and sparks. Contact with other chemicals
Incompatible Materials	Strong oxidizing agents. Strong acids. Strong bases.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke)

# **11. TOXICOLOGICAL INFORMATION**

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date	04-24-2012
--------------	------------

Revision Date 07-03-2018

Revision Number 3.1

### Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information
Inhalation	May cause irritation of respiratory tract.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	May cause irritation.
Ingestion	There is no data available for this product.

#### Component Information

Chemical name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Diacetone alcohol	> 4 g/kg (Rat)	= 13630 mg/kg (Rabbit) = 13500	> 7.23 g/m³ (Rat)8 h
123-42-2		mg/kg (Rabbit)	
Butylated Hydroxy Toluene	> 2930 mg/kg (Rat)	> 2000 mg/kg (Rat)	-
128-37-0			

#### Information on toxicological effects

#### Symptoms

No information available.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

The producer of "1251" declares that it contains less than 3% DMSO extractable material by IP-346

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
Target Organ Effects	Central nervous system (CNS), Respiratory system, Eyes, Liver, Skin.

### Numerical measures of toxicity - Product Information

#### The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	5048 mg/kg
ATEmix (dermal)	2026 mg/kg
ATEmix (inhalation-dust/mist)	29.8 mg/l

# 12. ECOLOGICAL INFORMATION

## Ecotoxicity

Chemical name	Algae/aquatic plants	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to daphnia and other aquatic invertebrates
Diacetone alcohol	-	LC50= 420 mg/L Lepomis	-	EC50 = 8750 mg/L 24 h

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

## Issuing Date 04-24-2012

Revision Date 07-03-2018

Revision Number 3.1

123-42-2	macrochirus 96 h		
	EC50 = 6 mg/L 72 h EC50 >		
128-37-0	0.42 mg/L 72 h		
Persistence and Degrad	ability No information available.		
<b>Bioaccumulation</b>	· ·		
<u>Mobility</u>	ty The product is insoluble and floats on water.		
Other Adverse Effects	Other Adverse Effects No information available		
13. DISPOSAL CONSIDERATIONS			
Waste treatment method	<u>S</u>		
Waste Disposal Methods	ethods Dispose of in accordance with local regulations.		
Contaminated Packaging	Do not re-use empty containers. Empty containers should be taken to an approved waste handling site for recycling or disposal.		

# **14. TRANSPORT INFORMATION**

DOT

Not regulated

15. REGULATORY INFORMATION		
International Inventorio	es	
TSCA	Complies	
DSL/NDSL	Not determined	
NDSL	Complies	
EINECS	Not determined	
ELINCS	Not determined	
ENCS	Not determined	
IECSC	Complies	
KECL	Not determined	
PICCS	Complies	
AICS	Complies	

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances

# 1251 ALMASOL® HIGH TEMPERATURE LUBRICANT

Issuing Date 04-24-2012

Revision Date 07-03-2018

Revision Number 3.1

IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

## U.S. Federal Regulations

### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories	
Acute Health Hazard	

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

#### CERCLA

This material does not contain any components with a CERCLA RQ.

## U.S. State Regulations

#### **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

This product does not contain any substances regulated by state right-to-know regulations

NFPA	Health hazard 1	Flammability 1	S	Stability 1
		i lannability		

## 16. OTHER INFORMATION

Issuing Date04-24-2012Revision Date07-03-2018Reason for revisionUpdate to Format.Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

SDS is available at www.LElubricants.com

End of Safety Data Sheet